

GasAlertMicro 5 PID

VOCs (PID), H₂S, CO, O₂, SO₂, PH₃, NH₃, NO₂, HCN, Cl₂, ClO₂, O₃, and Combustibles



Five-Gas Detector



Protect Yourself

- △ Smaller and over 50% lighter than competitive instruments
- △ Water-resistant design in an integral concussion-proof enclosure
- △ Continuous LCD shows simultaneous gas concentrations for five gases
- △ 0 - 1000 ppm measurement of VOCs (Volatile Organic Compounds)
- △ Integral motorized pump option for remote sampling
- △ Two power options: AA alkaline or rechargeable hot-swappable battery packs
- △ Provides 95 dB alarm tone and two bright wide-angled alarm bars
- △ Equipped with internal vibrating alarm for high noise areas
- △ Multi-language support in English, French, German, Spanish, and Portuguese
- △ Three backlight options: standard—activates in low light (auto), in alarm (auto) and reactivates on-demand; alarm only—activates in alarm conditions and reactivates on-demand; stealth mode
- △ Four alarm levels: instantaneous Low and High Alarm for all gases; TWA (time-weighted average) and STEL (short-term exposure limit) for VOCs and toxic gases
- △ Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- △ Records TWA, STEL, and maximum exposures to gas and displays readings on command
- △ User selectable field options include: PID / combustible correction factor, language selection, confidence beep, span level, set TWA/STEL calculation choice, set calibration due date, pass code protection, latching alarm, "SAFE" display function, stealth mode, and selectable ppm resolution for some gases (e.g. SO₂ 0.1 ppm)
- △ Full function self-test of: sensor, battery and circuit integrity; and audible/visual alarms
- △ Compatible with BW's MicroDock II — automated test and calibration station



GasAlertMicro 5 PID with integrally attached pump

Water Resistant



Optional rechargeable battery and slipp-in cradle charger



Ordering Information

GasAlertMicro 5 PID is delivered ready for use with sensors (as specified), sensor compartment cover for diffusion operation, battery (as specified), stainless steel alligator clip, calibration cap/hose, 2 extra electrode stacks, instructions in local languages and interactive training CD.

Battery/Charger Options

Three AA alkaline batteries
Rechargeable battery pack and desktop/wall mountable slipp-in cradle charger

User-Downloadable Datalogger Option

Datalogging versions include 32 MB MMC card, software and an IR port for use with the MicroDock II automated calibration and test station.

Pump Option

Includes detector, standard accessories plus integrally attached motorized pump and cover (installed), 12 in./30 cm sample probe with hydrophobic barrier (water trap) and particulate filters, 5 ft./1.5 m sampling tubing, five spare particulate filters, and one spare water trap filter.

Value Added Confined Space Kits

Kits include detector, standard accessories plus a hard-sided, foam-lined carrying case, 10 ft./3 m sampling hose, sample probe, battery power (as specified), 34 L calibration gas cylinder(s) with regulator(s).

Accessories

MMC USB Reader
Manual Aspirator Pump
MicroDock II—Automatic Calibration and Test Station
Vehicle Charger
Carrying Holster

www.gasmonitors.com

Email: info@bwt.net



GasAlertMicro 5 PID

VOCs (PID), H₂S, CO, O₂, SO₂, PH₃, NH₃, NO₂, HCN, Cl₂, ClO₂, O₃, and Combustibles

Five-Gas Detector

GasAlertMicro 5 PID portable gas detector simultaneously monitors up to five atmospheric hazards including volatile organic compounds (VOCs), oxygen, combustible gas (% LEL), and a wide selection of individual electrochemical toxic sensors. Compact and lightweight, **GasAlertMicro 5 PID** activates audible, visual and vibrating alarms in the event of a low, high, TWA or STEL alarm condition.

VOCs present multiple potential threats in the workplace environment. VOCs are characterized by their tendency to evaporate easily at room temperature and include substances such as solvents, paint thinners, benzene, butadiene, hexane, toluene, as well as vapors associated with fuels such as gasoline, diesel, heating oil, kerosene, and jet fuel. The **GasAlertMicro 5 PID**'s integrated photoionization detector (PID) enables sensitive broad spectrum monitoring of volatile organic contaminants.

Highly configurable to suit a range of applications, **GasAlertMicro 5 PID** comes as a diffusion or pumped instrument; with either alkaline or NiMH rechargeable hot-swappable battery pack and has optional datalogging capabilities. Standard features include confidence beep, automatic calibration, full function self-test, and an extended selection of user-settable field options.



For further information:

1-888-749-8878 USA
 1-800-663-4164 Canada
 +44 (0)1295 700 300 Europe
 +33 (0) 442 98 17 70 France
 +971-4-8871766 Middle East
 +61-3-9464-2770 Australia
 +86 10 8256 4525 China
 +65 6748 4915 South East Asia
 +1-403-248-9226 Other Countries

Corporate Headquarters

2840 - 2 Avenue S.E.
 Calgary, AB, Canada T2A 7X9
 Phone: 1-403-248-9226
 Fax: 1-403-273-3708

E-mail: info@bwt.net.com
 www.gasmonitors.com

BW1105-01-01-00-8.25x11-20050627-5789-5

SPECIFICATIONS

DETECTOR: 1, 2, 3, 4, or 5-gas detector

Gas	Measuring Range	Default Resolution	High Resolution	TWA	STEL	LOW	HIGH
O ₂	0-30.0%	0.50%	N/A	N/A	N/A	19.5	23.5
H ₂ S	0-300 ppm	1.0 ppm	0.1 ppm	10	15	10	15
CO	0-999 ppm	1.0 ppm	N/A	35	50	35	200
TwinTox (H ₂ S)	0-300 ppm	1.0 ppm	0.1 ppm	10	15	10	15
TwinTox (CO)	0-500 ppm	1.0 ppm	N/A	35	50	35	200
PH ₃	0-5.0 ppm	1.0 ppm	0.1 ppm	0.3	1.0	0.3	1.0
SO ₂	0-100 ppm	1.0 ppm	0.1 ppm	2	5	2	5
NO ₂	0-99.9 ppm	1.0 ppm	0.1 ppm	2.0	5.0	2.0	5.0
HCN	0-30.0 ppm	1.0 ppm	0.1 ppm	4.7	10.0	4.7	10.0
Cl ₂	0-50.0 ppm	1.0 ppm	0.1 ppm	0.5	1.0	0.5	1.0
NH ₃	0-100 ppm	1.0 ppm	0.1 ppm	25	35	25	50
ClO ₂	0-1.00 ppm	0.1 ppm	0.01 ppm	0.1	0.3	0.1	0.3
O ₃	0-1.00 ppm	0.1 ppm	0.01 ppm	0.1	0.1	0.1	0.1
VOC	0-1000 ppm	1 ppm	N/A	50	100	50	100
LEL	0-100% LEL 0-5.0% v/v	1%	N/A	N/A	N/A	10%	20%

Auto zero: Yes
 Calibration: Automatic
 Backlight: Standard Mode: low light (auto); alarm condition (auto); reactivation on demand
 Alarm Only Mode: alarm condition (auto); reactivation on demand
 Stealth Mode: backlight inactive; audible and visual alarms silenced
 Sensor: PID (VOC) 10.6 eV lamp; plug-in, electrochemical cell (toxic and oxygen); catalytic (LEL)
 User field options: Confidence beep, set STEL period, force calibration on start-up, enable / disable sensor, pass code protection, latching alarms, span level, passed calibration user-lockout option, "SAFE" display function, stealth mode, fast pump, oxygen auto-cal on start-up, alarm only backlight mode, combustible gas measurement (% LEL or % by volume methane), LCD language option, STEL calculation choice, TWA calculation choice, PID / combustible correction factor options, user-settable calibration gas level, high resolution, clock
 Pump: Tubing length up to 100 ft. / 30 m (50 ft. / 15 m standard) with user options
ALARM INDICATORS: Clearly advises alarm conditions with audible, visual, and vibrator alarms
 Visual alarms: Two flashing alarm bars visible from all angles
 LCD indicates gas present and alarm levels encountered
 Audible alarm: Typically 95 dB at 1 ft. / 30 cm variable pulsed audible alarm
 Vibrator alarm: Pulses warning in gas alarm conditions, or for any status alarms
 Status alarms: Low battery, over range, multiple gas / pump and failed or missing sensor
ALARM LEVELS: Instantaneous Low Alarm for all gases; Instantaneous High Alarm for all gases; TWA (time-weighted average) and STEL (short-term exposure limit) for toxics/VOCs
LCD: Continuous, alphanumeric gas readout and status display advises:
 Gases monitored: VOCs (PID), H₂S, CO, O₂, SO₂, PH₃, NO₂, NH₃, HCN, Cl₂, ClO₂, O₃ and/or combustibles (0-100% LEL or 0-5.0% methane)
 Gas concentration: Simultaneously and continuously displays gas concentration(s) for all sensors (in ppm, % LEL, or % v/v)
 Peak (max)/STEL/TWA ppm or %: Records exposures and displays on demand
 Alarm setpoints: Displayed on activation and on demand
 Calibration due date: Days remaining on start-up
 Clock: Real-time clock setting displayed on start-up
TESTS:
 Full function self-test: Sensor integrity, circuitry, battery and audible/visual alarms on activation
 Battery: Continuous
GENERAL SPECIFICATIONS: Rugged, composite material; two-shot molded polymer case with integral anti-shock boot
 Operating temperature: 14 to 104°F / -10 to 40°C VOC (PID); -4 to 122°F / -20 to 50°C other gases
 Humidity: 0 - 95% RH (non-condensing)
 EMI/RFI: Complies with EMC Directive 89/336/EEC
 Protection: Highly water resistant and dust proof housing
 Battery Options: 12 hours on three AA alkaline cells or 10 hours on rechargeable "hot-swappable" battery pack when equipped with PID, oxygen, combustible and TwinTox (H₂S/CO) sensor
 Size: 5.7 x 2.9 x 1.5 in. / 14.5 x 7.4 x 3.8 cm
 Weight: 13.1 oz. / 370 g
WARRANTY: Full 2-year warranty including all sensors (1 year PID lamp and NH₃ sensor)
DATALOGGER OPTIONS: User-downloadable datalogger
 Data recorder: All events and occurrences (calibration zero adjustment, calibration span adjustment, gas readings, TWA, STEL, alarm condition, failures detected by the microprocessor).
 Sampling rate: Factory set at 5-second intervals and user-settable from 1 to 127-second intervals
 Storage: 2 months of continuous data at 5 second intervals via 32 MB Flash MMC card (64 MB and 128 MB cards also available); when full, the wrap-around feature replaces oldest data with most recent data

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

RATINGS AND CERTIFICATIONS: Class I, Div. 1, Gr. A, B, C, D
 (Intrinsic safety) American Bureau of Shipping

ATEX: II 1 G T4
 EEx ia IIC T4
 IECEx: Ex ia IIC T4



Brave Engineering Ltd.

127/13 Moo 12 Raminthra Rd., Klongkum, Bungkum, Bangkok 10230 Thailand.
 Tel: +66(0)2944-4679, Fax: +66(0)2944-4920, Email: sales@braveengineering.com
 Website: http://www.braveengineering.com