



# GasAlertMicro 5

H<sub>2</sub>S, CO, O<sub>2</sub>, SO<sub>2</sub>, PH<sub>3</sub>, NH<sub>3</sub>, NO<sub>2</sub>,  
HCN, Cl<sub>2</sub>, ClO<sub>2</sub>, O<sub>3</sub>, and Combustibles

## Five-Gas Detector



### Protect Yourself

- △ Smaller and over 50% lighter than competitive instruments
- △ Water-resistant design in an integral concussion-proof enclosure
- △ Continuous LCD shows simultaneous gas concentrations for five gases
- △ Integral motorized pump option for remote sampling
- △ Two power options: AA alkaline or rechargeable hot-swappable battery packs
- △ Provides 95 dB alarm tone and two bright wide-angled alarm bars
- △ Equipped with internal vibrating alarm for high noise areas
- △ Multi-language support in English, French, German, Spanish, and Portuguese
- △ Three backlight options: standard—activates in low light (auto), in alarm (auto) and reactivates on-demand; alarm only—activates in alarm conditions and reactivates on-demand; stealth mode
- △ Four alarm levels: instantaneous Low and High Alarm for all gases; TWA (time-weighted average) and STEL (short-term exposure limit) for toxic gases
- △ Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- △ Records TWA, STEL, and maximum exposures to gas and displays readings on command
- △ User selectable field options include: language selection, confidence beep, span level, set TWA/STEL calculation choice, set calibration due date, pass code protection, latching alarm, "SAFE" display function, stealth mode, and selectable ppm resolution for some gases (e.g. SO<sub>2</sub> 0.1 ppm)
- △ Full function self-test of: sensor, battery and circuit integrity; and audible/visual alarms
- △ Compatible with BW's MicroDock II — automated test and calibration station



**Water  
Resistant**



**GasAlertMicro 5** with integrally attached pump



Optional rechargeable battery and slip-in cradle charger

### Ordering Information

GasAlertMicro 5 is delivered ready for use with sensors (as specified), sensor compartment cover for diffusion operation, battery (as specified), stainless steel alligator belt clip, calibration hose/cap, instructions in local languages and interactive training CD.

#### Battery/Charger Options

Three AA alkaline batteries  
Rechargeable battery pack and desktop/wall mountable slip-in cradle charger

#### User-Downloadable Datalogger Option

Datalogging versions include 32 MB MMC card, software and an IR port for use with the MicroDock II automated calibration and test station.

#### Pump Option

Includes detector, standard accessories plus integrally attached motorized pump and cover (installed), 12 in./30 cm sample probe with hydrophobic barrier (water trap) and particulate filters, 5 ft./1.5 m sampling tubing, five spare particulate filters, and one spare water trap filter.

#### Value Added Confined Space Kits

Kits include detector, standard accessories plus a hard-sided, foam-lined carrying case, 10 ft./3 m sampling hose, sample probe, battery power (as specified), 34 L calibration gas cylinder(s) with regulator(s).

#### Accessories

MMC USB Reader  
Manual Aspirator Pump  
Vehicle Charger  
Carrying Holster  
MicroDock II—Automatic Calibration and Test Station

[www.gasmonitors.com](http://www.gasmonitors.com)

Email: [info@bwt.net](mailto:info@bwt.net)

# GasAlertMicro 5

H<sub>2</sub>S, CO, O<sub>2</sub>, SO<sub>2</sub>, PH<sub>3</sub>, NH<sub>3</sub>,  
NO<sub>2</sub>, HCN, Cl<sub>2</sub>, ClO<sub>2</sub>, O<sub>3</sub>,  
and Combustibles

## Five-Gas Detector

**GasAlertMicro 5** portable gas detector simultaneously monitors and displays up to five potential atmospheric hazards including oxygen, combustible gases and a range of toxic gases. Compact and lightweight, **GasAlertMicro 5** adds multi-gas detection to BW Technologies' water-resistant line of detectors. Audible, visual and vibrator alarms activate in the event of a low, high, TWA or STEL alarm condition. An optional motorized pump is available.

Beyond features that come standard with BW portable instruments such as confidence beep, full function self test, automatic calibration and passcode protection, **GasAlertMicro 5** offers an extended selection of user-settable field options now including: stealth mode, backlight options, selectable ppm resolution, STEL / TWA measurement choice, combustible correction factor options, user-settable calibration gas concentrations and multi-language support.

## SPECIFICATIONS

DETECTOR: 1, 2, 3, 4, or 5-gas detector


Gas	Measuring Range	Default Resolution	High Resolution	TWA	STEL	LOW	HIGH
O <sub>2</sub>	0-30.0%	0.50%	N/A	N/A	N/A	19.5	23.5
H <sub>2</sub> S	0-300 ppm	1.0 ppm	0.1 ppm	10	15	10	15
CO	0-999 ppm	1.0 ppm	N/A	35	50	35	200
TwinTox (H <sub>2</sub> S)	0-300 ppm	1.0 ppm	0.1 ppm	10	15	10	15
TwinTox (CO)	0-500 ppm	1.0 ppm	N/A	35	50	35	200
PH <sub>3</sub>	0-5.0 ppm	1.0 ppm	0.1 ppm	0.3	1.0	0.3	1.0
SO <sub>2</sub>	0-100 ppm	1.0 ppm	0.1 ppm	2	5	2	5
NO <sub>2</sub>	0-99.9 ppm	1.0 ppm	0.1 ppm	2.0	5.0	2.0	5.0
HCN	0-30.0 ppm	1.0 ppm	0.1 ppm	4.7	10.0	4.7	10.0
Cl <sub>2</sub>	0-50.0 ppm	1.0 ppm	0.1 ppm	0.5	1.0	0.5	1.0
NH <sub>3</sub>	0-100 ppm	1.0 ppm	0.1 ppm	25	35	25	50
ClO <sub>2</sub>	0-1.00 ppm	0.1 ppm	0.01 ppm	0.1	0.3	0.1	0.3
O <sub>3</sub>	0-1.00 ppm	0.1 ppm	0.01 ppm	0.1	0.1	0.1	0.1
LEL	0-100% LEL 0-5.0% v/v	1%	N/A	N/A	N/A	10%	20%

Auto zero: Yes  
 Calibration: Automatic  
 Backlight: Standard Mode: low light (auto); alarm condition (auto); reactivation on demand  
 Alarm Only Mode: alarm condition (auto); reactivation on demand  
 Stealth Mode: backlight inactive; audible and visual alarms silenced  
 Sensor: Plug-in, electrochemical cell (toxic and oxygen); catalytic (LEL)  
 User field options: Confidence beep, set STEL period, force calibration on start-up, enable / disable sensor, pass code protection, latching alarms, span level, passed calibration user-lockout option, "SAFE" display function, stealth mode, fast pump, oxygen auto-cal on start-up, alarm only backlight mode, combustible gas measurement (% LEL or % by volume methane), LCD language option, STEL calculation choice, TWA calculation choice, combustible correction factor options, user-settable calibration gas level, high resolution, clock  
 Pump: Tubing length up to 100 ft. / 30 m (50 ft. / 15 m standard) with user options  
**ALARM INDICATORS:**  
 Clearly advises alarm conditions with audible, visual, and vibrator alarms  
 Visual alarms: Two flashing alarm bars visible from all angles  
 LCD indicates gas present and alarm levels encountered  
 Audible alarm: Typically 95 dB at 1 ft. / 30 cm variable pulsed audible alarm  
 Vibrator alarm: Pulses warning in gas alarm conditions, or for any status alarms  
 Status alarms: Low battery, over range, multiple gas / pump and failed or missing sensor  
**ALARM LEVELS:**  
 Instantaneous Low Alarm for all gases; Instantaneous High Alarm for all gases; TWA (time-weighted average) and STEL (short-term exposure limit) for toxics  
**LCD:**  
 Continuous, alphanumeric gas readout and status display advises:  
**Gases monitored:** H<sub>2</sub>S, CO, O<sub>2</sub>, SO<sub>2</sub>, PH<sub>3</sub>, NO<sub>2</sub>, NH<sub>3</sub>, HCN, Cl<sub>2</sub>, ClO<sub>2</sub>, O<sub>3</sub>, and/or combustibles (0-100% LEL or 0-5.0% methane)  
**Gas concentration:** Simultaneously and continuously displays gas concentration(s) for all sensors (in ppm, % LEL, or % v/v)  
 Peak (max)/STEL/  
 TWA ppm or %: Records exposures and displays on demand  
 Alarm setpoints: Displayed on activation and on demand  
 Calibration due date: Days remaining on start-up  
 Clock: Real-time clock setting displayed on start-up  
**TESTS:**  
 Full function self-test: Sensor integrity, circuitry, battery and audible/visual alarms on activation  
 Battery: Continuous

**GENERAL SPECIFICATIONS:** Rugged, composite material; two-shot molded polymer case with integral anti-shock boot  
**Operating temperature:** -4 to 122°F / -20 to 50°C  
**Humidity:** 0 - 95% RH (non-condensing)  
**EMI/RFI:** Complies with EMC Directive 89/336/EEC  
**Protection:** Highly water resistant and dust proof housing  
**Battery Options:** 23 hours on three AA alkaline cells or 20 hours on rechargeable "hot-swappable" battery pack when equipped with oxygen, combustible, TwinTox (H<sub>2</sub>S/CO) and one additional toxic sensor  
**Size:** 5.7 x 2.9 x 1.5 in. / 14.5 x 7.4 x 3.8 cm  
**Weight:** 13.1 oz. / 370 g  
**WARRANTY:** Full 2-year warranty including all sensors (1 year NH<sub>3</sub> sensor)  
**DATALOGGER OPTIONS:** User-downloadable datalogger  
**Data recorder:** All events and occurrences (calibration zero adjustment, calibration span adjustment, gas readings, TWA, STEL, alarm condition, failures detected by the microprocessor).  
**Sampling rate:** Factory set at 5-second intervals and user-settable from 1 to 127-second intervals  
**Storage:** 2 months of continuous data at 5 second intervals via 32 MB Flash MMC card

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

**RATINGS AND CERTIFICATIONS:**  Class I, Div. 1, Gr. A, B, C, D  
 (Intrinsic safety)  American Bureau of Shipping

**ATEX:** CE  II G T4  
 EEx ia IIC T4  
**IECEx:** Ex ia IIC T4

"INNOVATORS IN GAS DETECTION"



### For further information:

1-888-749-8878 USA  
 1-800-663-4164 Canada  
 +44 (0) 1869 233004 Europe  
 +971-4-8871766 Middle East  
 +61-438-887-232 Australia  
 +852-2974-1783 China  
 +65-6465-4151 South East Asia  
 +1-403-248-9226 Other Countries

### Corporate Headquarters

2840 - 2 Avenue S.E.  
 Calgary, AB, Canada T2A 7X9  
 Phone: +1-403-248-9226  
 Fax: +1-403-273-3708

Email: info@bwt.net.com  
 www.gasmonitors.com

BW1078-01-01-00-8.25x11-20050630-5612-7



## Brave Engineering Ltd.

127/13 Moo 12 Raminthra Rd., Klongkum, Bungkum, Bangkok 10230 Thailand.  
 Tel: +66(0)2944-4679, Fax: +66(0)2944-4920, Email: sales@braveengineering.com  
 Website: http://www.braveengineering.com